

GEO MORPHOLOGICAL ,HYDROLOGICAL CHARACTERISTICS AND CROP PLANNING OF 19E/17 WATERSHED OF KANDHAMAL DISTRICT OF ODISHA, INDIA

G. Prasad*, R.Subudhi*& C R Subudhi**

*Student, CAET, OUAT, Bhubaneswar

**Professor, Dept. of SWCE, CAET, OUAT, Bhubaneswar, Odisha, India

ABSTRACT

This experiment was conducted at Dept.of Soil and Water Conservation and Engineering, CAET,OUAT, Bhubaneswar, Odisha, India. It was conducted to estimate the hydrologic parameters of 19E/17 watershed of Kandhamal district under North- eastern ghat zone . In this study the various hydrological parameters of 19E/17 watershed of Kandhamal district was found out using the toposheet. To carry out this experiment the contour lines were marked to demarcate the high points and the delineation of watershed was done with this the stream line was also marked which carry the runoff from the entire catchment area. Various features of hydrological parameters were found out. Simulating these data the runoff volume could be calculated and the possibilities of construction of river valley projects in that area can be obtained. The shape of the watershed is fern shape. Due to narrow catchments the peak flood intensity is reduced since discharges are likely to be distributed over a long period of time. The drainage density (D_d) was found to be 9.48Km^{-1} which is a high value and indicates that the basin is moderately impermeable and also high bifurcation ratio indicates higher D_d . It is affected by permeability, climate, vegetation, length of stream. The watershed planning and the cropping pattern of the watershed in the command area have been carried out.

INTRODUCTION

The watershed 19E/17 is coming under Kandhamal district of Odisha. It has light textured well drained upland soils and comes under North Eastern Ghat zone of Odisha. The intermittent dry spell and terminal drought affects the crop productivity in most of the years. About 25% of the rainfall is lost as runoff. Harvesting of the runoff water in dams will conserve the runoff water as well as minimise the soil loss of the watershed. This dams will increase the cropping intensity of the watershed area as well as increase the profit of the farmers.

Watershed based planning will solve this problem. So hydrological parameters will be helpful for this. Ramser (1927), Ghosh (1959), Chow (1964) Nemec (1973) Subudhi (1985), Subudhi (1995), Strahler (1952) & Chorley et al (1985) expressed different types of relationship among the hydrological parameters. Drainage morphology is defined as a measurement of linear areal and relief characteristics of any drainage basin (Clarke 1966) Drainage morphometry was first initiated by Horton (1932).

Protection, improvement and rehabilitation of watersheds are of critical importance to achievement overall watershed development goals. This can be possible only after collecting existing data, analysing and identifying major watershed problems and considering management possibilities. Keeping in view the watershed, developmental and management work has been performed. Generally, the stored water in the dam was not utilised according to the irrigation and water requirement of crops in different seasons. Due to the improper

planning the farmers grow only one crop instead of two to three crops. So to solve this problem software developed by Hembram & Subudhi (2016) was used to calculate water and irrigation requirement of different crops and for every watershed the determination of cropping pattern to increase the cropping intensity of the farmers of this tribal area. So taking into considerations of above problems following objectives were selected:

1. To obtain the different watershed characteristics of watershed.
2. To obtain the cropping pattern in the command area of the dam.

MATERIALS AND METHODS

Description of watershed

This study was carried out at Dept. of Soil and Water Conservation Engineering, College of Agricultural Engineering and Technology, Odisha University of Agriculture and Technology, Bhubaneswar, Odisha during 2019. The 67E/17 watershed is in Kandhamal district of Odisha (Fig 1), situated between the longitude of 84°5' to 84°0' and latitude 20°42' to 20°45' with a geographical area of 2.35sq km.

The Kandhamal district is under North eastern ghat zone, with elevation of 300m to 1100m above mean sea level. The geographical area is 7654 sq km and forest area of 3624 sq km. It has sub tropical climate characterized by hot and dry summer, cool and humid monsoon and cold and dry winter. The soil type is red late rite, light textured, porous and acidic. The percentage of irrigation done in *Kharif* and *Rabi* is 12

and 4.5% respectively. The monsoon scenario of Phulbani normally starts in the second week of June and its cessation in the second week of October .The total

rainfall is 140 7.4mm with number of rainy days as 65 (Table 1). The month of August received highest rainfall as well as highest rainy days.

Table 1 Normal rainfall and rainy days at Kandhamal

Sl.No.	Month	Monthly normal	Normal rainy days
1	January	9.5	1
2	February	14.2	1
3	March	20.1	1
4	April	31	2
5	May	57.3	3
6	June	188.7	9
7	July	350.4	15
8	August	383.2	15
9	September	228.2	11
10	October	95.7	5
11	November	24	1
12	December	5	1
Total		1407.4	65

The outlet of the watershed was first marked and then the concentric contour lines were demarcated which shows the high points, joining all the points the delineation of the watershed was done. Delineation is part of the process known as watershed segmentation, i.e., dividing the watershed into discrete land and channel segments to analyze watershed behaviour. This is performed using the tracing paper from the toposheet. The

length of run was calculated using a thread and area using graph paper.

Geomorphological characteristics of watershed:

The quatitative land form analysis is undertaken for the developed watershed in which flowing water and associated mass gravity movements acting over long periods of time are responsible for development of surface geometry

Linear Aspects of drainage networks

Stream Order:

The stream order represents the degree of stream branching within a watershed. Each length of stream is designated by its order.

Bifurcation Ratio:

The bifurcation ratio is defined as the ratio of the number of streams of any order to the number of streams of the next higher order.

Stream length:

The extent of stream length in a watershed reveals the characteristics size of various components of drainage network and its contributing surface area.

Stream length ratio:

Stream length ratio (RL) is defined as the average length of streams of any order to the average length of streams of the next lower order.

Areal Aspects of watershed

Total basin area:

The area A_u of a basin of order u is the total area projected on a horizontal plane contributing the overland flow to the streams of given order plus all the tributaries of lower order.

Basin Shape:

The basin shape is the shape of projected surface on the horizontal plane of basin

shape. The basin shape has a significant effect on stream discharge characteristics.

The quantitative expression of basin can be characterized by

Form factor, circulatory ratio, elongation ratio

Form factor (Rf): The ratio of basin area to the square of the basin length.

Circulatory Ratio (Rc): Circulatory ratio is the ratio of basin area (A_u) to the area of the circle having equal perimeter as the perimeter of the drainage basin.

Elongation ratio (RI): It is the ratio of diameter of a circle having same area as the basin to the maximum basin length.

Drainage Density (Dd):

The drainage density is defined as the ratio of the total length of all streams of all orders within a watershed to the total area of the watershed.

Stream frequency:

It is the number of stream segments per unit area of watershed.

Relief Ratio: It is the ratio of relief (elevation difference between reference points located in the drainage basin) to the horizontal distance on which relief was measured.




Figure 1 Location map of 19E/17 watershed

The crop water requirement (CWR) and irrigation requirement (IR) of various crops were calculated using a web based software. Relevant crop coefficients (K_c), duration of crops and cropping pattern were used to calculate CWR from E_{To} . These coefficients present the relationship between references (E_{To}) and crop evapotranspiration (ET_{crop}) or $ET_{crop} = K_c * E_{To}$. The covered area of all crops (canopy cover) was collected. The K_c values were taken from FAO. Crop water and irrigation requirement for majors crops grown in three seasons, *summer* (rice, sugarcane, sunflower and watermelon), *kharif* (long duration

paddy, medium duration paddy, short duration paddy, banana, mango, maize, brinjal and ladiesfinger) and *rabi* (green gram, black gram, groundnut, maize, sesamum, mustard, tomato, potato, cabbage and cauliflower) of the all agro-climatic zones were calculated. By using the software a farmer can find out the water requirement and irrigation requirement by giving the crop name according to their season and duration of crop Hembram P. & Subudhi C.R. (2016).

RESULT AND DISCUSSION:

The different linear aspects were presented in Table 2.

Table 2: Linear Aspects of Drainage Networks

Sl no.	Parameters	Abbreviation	Values
1	Maximum length	L	2.45km
2	Maximum width	W	1.5 km
3	Stream length ratio	R_L	0.58
4	Stream bifurcation Ratio	R_b	4.5
5	Mean bifurcation ratio	R_{bm}	2.5
6	Length of run		2.7 km

7	Length of overland flow	L_g	0.08 km
8	Stream length	L_u	16.9 km 2.11 km
i	1 st order		
ii	2 nd order		
9	Mean stream length	L_{sm}	5.7 km 2.2 km
i	1 st order		
ii	2 nd order		

The different areal aspects were presented in Table 3.

Table 3 Areal Aspects of 19 E/17 watershed

S/no.	Parameters	Abbreviation	Values
1.	Area	A	2.35 km ²
2	Shape	-	Fern shape
3	Drainage density A	D_d	9.48 Km ⁻¹
4	Stream frequency A	F_s	5.10 km ⁻²
5	Drainage texture A	D_t	1.28 km ⁻²
6	Circulatory Ratio A	R_c	0.25
7	Form Factor A	R_f	0.42
8	Elongation Ratio A	R_e	0.812
9	Compactness coefficient A	C_c	1.72
10	Length/width ratio	-	1.42

Relief aspects of drainage basin: Relief Ratio: (R_h) =0.18

From the above study we observed that

- After delineating the watershed the shape of the watershed was found to be fern shaped.
 - The tributaries are of different lengths and meet the main stream at regular intervals.
 - In these narrow catchments the peak flood intensity is reduced since discharges are likely to be distributed over a long period of time.
 - The tributaries are distributed evenly.
 - Cause of flood is minimal.
 - All the tributaries are of different sizes.
- The length of run was found to be 2.7 km which indicates good surface runoff of the study area
- The drainage density (D_d) was found to be 9.48Km⁻¹ which is a high value and indicates that the basin is moderately

impermeable and also high bifurcation ratio indicates higher D_d . It is affected by permeability, climate, vegetation, length of stream.

- The higher value of stream frequency i.e.4.5 km⁻² indicates that there is a quick removal of surface flow of the runoff in the watershed.
- The form factor (A/Lb^2) i.e.0.42 indicates that the watershed is elongated and has longer duration of flow.
- The circulatory ratio i.e.0.25 indicates that the watershed is in an elongated shape
- As the elongation ratio should be between 0.6 to 1.0 .values close to 1 are typically of regions of high relief whereas, that from 0.6 to 0.8 are associated with high relief and steep ground slope. This ratio is found out to be 0.812, the

watershed is considered to be of oval shaped and has high relief.

8. The compactness coefficient was found out to be 1.72 which indicates it has more deviation from the circular nature of watershed and it will have long

time of concentration before peak of flow.

Taking into consideration of above factors mentioned above watershed and crop planning will be made in this watershed.

Table 4: Irrigation and water requirement for different crops

Crops	<i>Kharif</i>		<i>Rabi</i>		<i>Summer</i>	
	Irrigation requirement (mm)	Water requirement (mm)	Irrigation requirement (mm)	Water Requirement (mm)	Irrigation requirement (mm)	Water requirement (mm)
Paddy (120days)	444	940	-	-	-	-
Mustard (90 days)	-	-	224	309	-	-
Tomato	-	-	-	-	480	598

i.The Cathment and command area was found out to be - 37 ha and 37 ha respectively.

ii.The Cropping area in *Kharif*- 37 ha, *Rabi*= 37 ha, *Summer*= 27.65 ha

So, the cropping pattern was planned as Paddy, Mustard, Tomato in *kharif*, *rabi* and *summer* seasons respectively according to the amount of rainfall the watershed receives every year. The water and irrigation requirement which was used by using software was shown in Table 4.

Conclusion

1. The shape of the watershed is fern shape . Due to narrow catchments the peak flood intensity is reduced since discharges are likely to be distributed over a long period of time.

2. The drainage density (D_d) was found to be 9.48Km^{-1} which is a high value and indicates that the basin is moderately impermeable and also high bifurcation ratio indicates higher D_d . It is affected by permeability, climate, vegetation, length of stream.

3. The cropping pattern was planned as Paddy, Mustard, Tomato in *kharif*, *rabi* and *summer*.

REFERENCES

Chorley , R.J. Schumm, S.A.Sugden, D.E. (1985) Geomorphology Methew and Co., Ltd. , London.

Chow, V.T.(1964) Handbook of applied hydrology , a compendium of water resources technology Mc Graw Hill Book Company, New York.

Clarke, J.J. (1966). Morphometry from map. Essays in geomorphology. Elsevier, New York, pp 235-274.

Ghosh, B.N.(1959) Food estimation J.Inst.Engr.(India), 40(1):391-393.

Hembram P. & Subudhi, C.R.(2016) Development of a software for water and irrigation requirement for major crops of north central plateau zone of odisha,

Unpublished M.Tech thesis , CAET, OUAT, Bhubaneswar.

Horton R.E. (1945) Erosional development of streams and their drainage basins: hydro physical approach to quantitative morphology. Bull Geol Soc Am 56:275-370.

Nemec, J.(1973) Basic hydrological concepts, Engineering hydrology Tata Mc Graw Hill Book Company, New York.

Ramser, C.C.(1927) Runoff from small agricultural areas. J.Agric.Res.34(9):797-823.

Strahler AN (1964) Quantitative geomorphology of basins & channel networks In. Chow V.T. (ed) Handbook of applied hydrology. Mc Graw Hill book company, New York.

Subudhi, C.R. (1984) Hydrological event analysis in upper Damodar valley. Unpublished M.Tech Thesis, I.I.T., Kharagpur.

Subudhi; C.R. (1995) Indian Journal of soil Conservation 23(3): 205-207.

